

Richard hourigan, inc.

esponding to the needs of industry since 1973

SBW-4130

OXYGEN SCAVENGER

Visit: www.TheWaterTreatmentStore.com

Description

Solid form, oxygen scavenger.

Function

This is a proprietary boiler water treatment containing decharacterized sodium sulfite, sodium lignosulfonate, bisulfite, and erythorbate. It reduces the potential for oxygen corrosion and general corrosion in boiler water systems.

Application/Feedrate

Fed at 30 ppm, 1 lb of product treats approximately 33,333 lbs of boiler blowdown (depending upon the amount of oxygen being removed mechanically). 1 case (48 lbs) is equivalent to 30 gallons of a conventional liquid product (approximately 300 lbs). Liquid equivalent comparative values will vary, dependent upon concentration.

Testing & Control

Testing	In Boiler Water
Sulfite	20 – 60 ppm

Feeding

Suggested use with SolvUltima™ mixing boards:

All Solv-all™ boards; Hydro Solv-Ultima™ series.

Packaging/Storage/Handling

Available in:

- Gallon containers – 1 case of 4 @ 48 lbs/case
- Sticks – 1 case of 30 @ 24 lbs/case

Follow MSDS. Properly stored product will remain effective for 24-36 months. Store in cool, dry area