

Richard hourigan, inc.

Responding to the needs of industry since 1973

SBW-4211

Visit: www.TheWaterTreatmentStore.com

BOILER TREATMENT
All-In-One (NO AMINE)

Description

Solid form, all-in-one boiler water treatment (no amine) for SOFTENED make-up water applications

Function

This is a proprietary boiler water treatment containing corrosion inhibitors (extra sulfite for situations where there is no DA or heater), scale control agents & alkalinity builders. All components conform to FDA Title 21, Section 173 Boiler Water Additives.

Application/Feedrate

Dosed at 60 ppm, 1 lb of product treats approximately 16,670 lbs of boiler blowdown. 1 case (48 lbs) is equivalent to 30 gallons of a conventional liquid product (approximately 300 lbs). Liquid equivalent comparative values will vary, dependent upon concentration.

Testing & Control

Testing	In Boiler Water
Sulfite	20 – 30 ppm
p-Alkalinity	250 – 600 ppm
Conductivity	See Manufacturer's Guidelines

Product Dissolving Data

See graph at right.

Maximum Solubility @ 80°F: **7.2%**

Feeding

Suggested use with SolvUltima™ mixing boards: All Solv-all™ boards; Hydro Solv-Ultima™ series.

Packaging/Storage/Handling

Available in:

- Gallon containers – 1 case of 4 @ 48 lbs/case

Follow MSDS. Properly stored product will remain effective for 24-36 months. Store in

