

Richard hourigan, inc.

Responding to the needs of industry since 1973

SCS-3200

CLOSED LOOP TREATMENT

Visit: www.TheWaterTreatmentStore.com

Description

Solid form, complete system corrosion inhibition treatment for chill water & hot water boilers. Contains silicates, borax, acrylates, phosphino corrosion inhibitor, and copper metal inhibitor, with a molybdate tracer for testing.

Function

This is a proprietary product to be used as a stand-alone treatment for corrosion inhibition in closed water systems. Contains no nitrites.

Packaging/Storage/Handling

Available in:

- **Gallon containers** – 1 case of 4 @ 48 lbs/case (SCS-3200)
- **Sticks** – 1 case of 30 @ 24 lbs/case (SCS-3200-S)

Follow MSDS. Properly stored product will remain effective for 24-36 months. Store in cool, dry area.

Application/Feedrate

- **Gallon containers** - 1 lb per 500 gallons water capacity
- **Sticks** - 1 water-soluble stick per 400 gallons water capacity

Testing & Control

MOLYBDATE (as Mo): 8 -10 ppm

Feeding

- **Gallon containers** - Suggested use with SolvUltima™ mixing boards: All Solv-all™ boards; Hydro Solv-Ultima™ series
- **Sticks** – Remove water soluble stick from corrugated shipping container and introduce into shot feeder or open tank. Dissolving rates will vary depending upon water consumption, temperature, and flow rate.
 - In water less than 50°F, the STX products should be fed to closed system via side stream filter with appropriate filter media in place.