

# Richard hourigan, inc.

---

esponding to the needs of industry since 1973

**SCS-3600-S**

**CLOSED SYSTEM CLEANER/PASSIVATOR**

Visit: [www.TheWaterTreatmentStore.com](http://www.TheWaterTreatmentStore.com)

**Description:**

Packaged in a stick form, designed to eliminate messy liquid additions to water systems. These are employed for pretreatment and shutdown cleaning of closed re-circulating systems. This product was designed to passivate & remove deposits of mill scale, oil and grease, or other fouling materials prior to placing the system into normal operating conditions.

**Application/Feedrate**

This product should be fed at the rate of 1 stick per 50 gallons of water volume. Product contains alkaline materials. Follow manufacturer suggested cleanout/boil-out procedure. pH may increase to excessive levels. Care should be taken to avoid contact with copper at high pH levels. NOTE: This product may cause foaming when fed at high levels.

**Testing & Control**

No test, add as suggested.

**Feeding**

Remove stick from corrugated packaging, and introduce into shot feeder or open tank. Dissolving rates will vary depending upon water composition, temperature, and flow rate.

**Packaging/Storage/Handling**

Packaged in 24 x one lb sticks (enclosed in individual water soluble bags, packaged in corrugated packs) per case. Case weighs 24 lbs. The diameter of each stick is approximately 2 inches, fitting into most screw top capped shot feeders. Follow MSDS. Properly stored product will remain effective 24 - 36 months. Store in cool, dry area.