



## VpCI™ ADDITIVES FOR FORMULATORS

PURCHASE THIS PRODUCT

VISIT THE WATER TREATMENT STORE TO VIEW THIS AND OTHER PRODUCTS

# Boiler Lizard™ Patent Pending

## VpCI™ Boiler Lay-up



### PRODUCT DESCRIPTION

Cortec's Boiler Lizard™ contains Vapor phase Corrosion Inhibitor (VpCI™) powder in a polyvinyl alcohol (PVA) water-soluble bag. The powder formulation is free of phosphates, heavy metals, nitrites and free amines. Designed for dry lay-up of boilers, the Boiler Lizard™ powder protects metals in enclosed spaces. The VpCIs™ vaporize and adsorb on all metal surfaces, reaching all recessed areas and interior cavities.

### FEATURES

- Provides continuous corrosion protection during dry lay-up period
- Protects ferrous metals and aluminum
- Provides protection in the vapor phase (void), liquid phase and the interface
- Up to 12 months protection
- Vapor phase inhibiting action protects inaccessible and recessed surfaces
- Requires little or no surface preparation for routine shutdown maintenance
- VpCI layer does not need to be removed prior to equipment start-up

- Eliminates need for other forms of protection including nitrogen blankets, silica gel and hydrazine
- Reduces chemical consumption and costs
- Safe for handling
- Biodegradable, non-toxic and non-irritating PVA bags
- Increases worker productivity and safety
- Formulation is free of phosphate, heavy metals, nitrites and free amines
- Protects up to 1,000 gallons system capacity per bag (5 yd<sup>3</sup> or 3.8 m<sup>3</sup>)

### METHOD OF APPLICATION

Completely drain and cool boiler down. Remove and discard outer protective water insoluble bag. Place Boiler Lizard flat in boiler and slit open the inner water soluble bag to begin total corrosion protection. Slit this inner bag 2" (5 cm) from one end to 2" (5 cm) from the other end. Seal all openings to the boiler internals. No product or inner bag removal is required prior to boiler start-up. When the boiler is put back in service, fill with water and employ common start-up procedure. The inner PVA bag will dissolve.

### DIMENSIONS

Tube	3" D x 37" H (8 cm x 94 cm)
Bag	4" W x 34" H (10 cm x 86 cm)

### PHYSICAL PROPERTIES OF POWDER

Appearance	White to off-white powder
pH	6.5-6.9 (1% aqueous)
Melting Point	371°-398°F (188°-203°C)

### PACKAGING AND STORAGE

Boiler Lizards™ are supplied in carton tubes (1 bag per tube). Store in sealed container in a dry warehouse. Do not store in conditions above 130°F (54°C). Shelf life is 2 years.

