


The V-10 Chemical Metering Pump


Purchase these from: www.TheWaterTreatmentStore.com



V-10 SIMPLEX

GENERAL INFORMATION


The V-10 is a high pressure, low volume, reciprocating plunger, positive displacement chemical metering pump. It is ideal for use in chemical feed to boilers, waste water treatment, the pulp and paper industry, and related applications where a controlled volume of chemical treatment is required.



V-10 DUPLEX

CONSTRUCTION

The V-10 is designed for trouble free operation with a minimum of maintenance. Precision inline boring of the base casting insures exact alignment of the drive mechanism and the piston head assembly, minimizing wear. The drive mechanism is a heavy duty speed reducer, available in a number of ratios. Any 56C frame motor can be mounted on the heavy duty speed reducer making it easy to match the V-10 pump to special environments or electrical characteristics. The V-10 pump head is precision machined and has a ground and polished piston and double ball check valves on the inlet and outlet. The pump head comes standard in carbon steel but is available in various grades of stainless steel and the packing seals are available in Buna N, Viton, and Teflon. V-10 pump heads are available in numerous piston sizes from 1/4" to 2" to cover various pumping ranges and all are interchangeable on the same pump base casting. The pump is also available with multiple heads



V-10 QUAD



V-10 VERTICAL DRIVE




V-10 VARIABLE SPEED

PISTON PUMP MODEL NUMBERS



V-10 SIMPLEX




V-10 DUPLEX



V-7 MINI-PUMP

1560-12-SS



MAXIMUM FULL STROKE OUTPUT PER PUMP HEAD SIZE AT VARIOUS STROKE RATES
VALUES BASED ON WATER
MINIMUM RECOMMENDED STROKE SETTING IS 20% OF MAXIMUM

MODEL

1	SIMPLEX-SINGLE DRIVE TO ONE PUMP HEAD
2	DUPLEX-SINGLE DRIVE TO TWO PUMP HEADS
3	TRIPLEX-SINGLE DRIVE TO THREE PUMP HEADS
4	QUAD-SINGLE DRIVE TO FOUR PUMP HEADS

PISTON SIZE

2	1/4" DIAMETER
3	3/8" DIAMETER
4	1/2" DIAMETER
5	5/8" DIAMETER
7	1 1/2" DIAMETER
8	1" DIAMETER
9	2" DIAMETER

STROKING RATE

60	SIXTY STROKES PER MINUTE
30	THIRTY STROKES PER MINUTE
18	EIGHTEEN STROKES PER MINUTE
12	TWELVE STROKES PER MINUTE
06	SIX STROKES PER MINUTE
01	ONE STROKE PER MINUTE

DRIVE

00	LESS ANY DRIVE AND BASEPLATE	NO DRIVE
0CD	LESS MOTOR (COUPLING DRIVE CONFIGURATION)	COUPLING DRIVE
0FM	LESS MOTOR (FLANGE MOUNT CONFIGURATION)	FLANGE MOUNT
3	1/2 HP 120/240 VAC EXPLOSION PROOF FAN COOLED	COUPLING DRIVE
4	1/2 HP 90 VDC TOTALLY ENCLOSED FAN COOLED	COUPLING DRIVE
6	1/2 HP 240/480 VAC EXPLOSION PROOF FAN COOLED	COUPLING DRIVE
7	1/2 HP 240/480 VAC TOTALLY ENCLOSED FAN COOLED	COUPLING DRIVE
8	1/2 HP 120/240 VAC TOTALLY ENCLOSED FAN COOLED	COUPLING DRIVE
12	1/3 HP 120/240 VAC TOTALLY ENCLOSED FAN COOLED	FLANGE MOUNT
12V	1/2 HP 120/240 VAC TOTALLY ENCLOSED FAN COOLED	FLANGE MOUNT
13	1/3 HP 120/240 VAC EXPLOSION PROOF FAN COOLED	FLANGE MOUNT
14	1/4 HP 90 VDC TOTALLY ENCLOSED NON-VENTILATED	FLANGE MOUNT
14V	1/2 HP 90 VDC TOTALLY ENCLOSED FAN COOLED	FLANGE MOUNT
15	1/4 HP 240/480 VAC TOTALLY ENCLOSED NON-VENTILATED	FLANGE MOUNT
15V	1/2 HP 240/480 VAC TOTALLY ENCLOSED FAN COOLED	FLANGE MOUNT
16	1/2 HP 240/480 VAC EXPLOSION PROOF FAN COOLED	FLANGE MOUNT
17	1/3 HP 575 VAC TOTALLY ENCLOSED FAN COOLED	FLANGE MOUNT
18	1/3 HP 115/230 VAC 50/60 HZ TOTALLY ENCLOSED FAN COOLED	FLANGE MOUNT
19	1/2 HP 240/480 VAC TOTALLY ENCLOSED NON-VENTILATED INVERTER DUTY	FLANGE MOUNT
20	1/2 HP 115/230 VAC TOTALLY ENCLOSED NON-VENTILATED SEVERE DUTY	FLANGE MOUNT

WET END

BLANK	CARBON STEEL
SS	303 STAINLESS STEEL
S6	316 STAINLESS STEEL
C20	ALLOY 20 STAINLESS STEEL
HC	ALLOY 276 STAINLESS STEEL

V-7 MINI PUMP

V-7-60	60 STROKES PER MINUTE	48 GPD MAX @ 100 PSI MAX	1/20 HP TEFC
V-7-30	30 STROKES PER MINUTE	24 GPD MAX @ 100 PSI MAX	1/20 HP TEFC
V-7-12	12 STROKES PER MINUTE	6 GPD MAX @ 100 PSI MAX	1/20 HP TEFC
V-7-6	6 STROKES PER MINUTE	3 GPD MAX @ 100 PSI MAX	1/20 HP TEFC
V-7-2	2 STROKES PER MINUTE	1 GPD MAX @ 100 PSI MAX	1/20 HP TEFC

1/4" DIA PISTON 1000 PSI MAX				
STROKE	FULL STROKE OUTPUT			
RATE	ML/MIN	GPH	GPD	
01	1	0.015	0.36	
06	6	0.1	2.4	
12	12	0.2	4.8	
18	18	0.3	7.2	
30	30	0.5	12	
60	60	1	24	

1" DIA PISTON 500 PSI MAX				
STROKE	FULL STROKE OUTPUT			
RATE	ML/MIN	GPH	GPD	
01	15	0.25	6	
06	90	1.5	36	
12	180	3	72	
18	270	4	96	
30	450	7	168	
60	900	14	336	

3/8" DIA PISTON 1000 PSI MAX				
STROKE	FULL STROKE OUTPUT			
RATE	ML/MIN	GPH	GPD	
01	1.66	0.026	0.62	
06	10	0.16	3.8	
12	20	0.32	7.6	
18	30	0.48	11.5	
30	50	0.8	19.2	
60	100	1.6	38.4	

1 1/2" DIA PISTON 100 PSI MAX				
STROKE	FULL STROKE OUTPUT			
RATE	ML/MIN	GPH	GPD	
01	30	0.5	12	
06	180	3	72	
12	360	6	144	
18	540	9	216	
30	900	15	360	
60	1800	30	720	

1/2" DIA PISTON 1000 PSI MAX				
STROKE	FULL STROKE OUTPUT			
RATE	ML/MIN	GPH	GPD	
01	3	0.05	1.2	
06	18	0.3	7.2	
12	36	0.6	14.4	
18	54	0.9	21.6	
30	94	1.5	36	
60	188	3	72	

2" DIA PISTON 100 PSI MAX				
STROKE	FULL STROKE OUTPUT			
RATE	ML/MIN	GPH	GPD	
01	60	1	24	
06	360	6	144	
12	720	12	288	
18	1080	18	432	
30	1800	30	720	
60	3600	60	1440	

5/8" DIA PISTON 1000 PSI MAX				
STROKE	FULL STROKE OUTPUT			
RATE	ML/MIN	GPH	GPD	
01	6	0.1	2.4	
06	36	0.6	14.4	
12	72	1.2	28.8	
18	108	1.8	43.2	
30	180	3	72	
60	360	6	144	

V-7 MINI-PUMP 100 PSI MAX				
STROKE	FULL STROKE OUTPUT			
RATE	ML/MIN	GPH	GPD	
2	2.5	0.04	1	
6	8	0.12	3	
12	15	0.25	6	
30	63	1	24	
60	126	2	48	